

TYPE, SIZE & LOCATION (T,S,&L) PROCEDURES
FOR BRIDGE REPLACEMENT PROJECTS

Prior to development of preliminary plans, a Type, Size, and Location (T,S,&L) study shall be presented to the Michigan Department of Transportation Local Agency Program (MDOT LAP) critical bridge unit for review. This T,S,&L plan will be used to determine acceptability for funding by MDOT LAP on the basic design. The intent of the T,S,&L is to obtain concurrence from appropriate parties prior to the preliminary design of the project, thus expediting the process and minimizing delay in project development.

I. SUBMITTAL

- A. Historic structure - For bridges eligible to be historic, a Finding of No Adverse Impact or a Finding of No Significant Impact (FONSI) must be granted prior to the T,S,&L submittal.
- B. Time frame - T,S,&L plans should be submitted to the MDOT LAP at least 4 months prior to the anticipated letting date.

II. REVIEW

- A. MDEQ - Send one copy of the T,S,&L plans to the Michigan Department of Environmental Quality (MDEQ), when applicable. An MDEQ permit application should be made concurrently with the T,S,&L submittal to MDOT LAP.
- B. Local Agency - T,S,&L plans are to be reviewed by the local agency prior to submittal to MDOT LAP. The local agency will then send one copy of the T,S,&L plans to MDOT LAP. Additional copies may be requested by MDOT LAP staff.
- C. Field Review - Depending on the complexity of the project, there may be a field review of the T,S,&L plans. This field review may be done at the request of the local agency or at the discretion of MDOT LAP.
- D. Review by other agencies - The office review and, if required, field review, may include the Federal Highway Administration (FHWA), Michigan Department of Environmental Quality, and other agencies, as required and requested, by MDOT LAP. Review of projects which are on the National Highway System with a total estimated cost over \$1,000,000, may include FHWA.

III. T,S,&L PLAN DEVELOPMENT

The proposed T,S,&L is to depict the most cost effective design which meets the engineering and environmental requirements. The T,S,&L plans may be presented on the General Plan of Site sheet. Other details and/or plan sheets may be included as required. These plans do not need to be elaborate as long as they convey the necessary information. The following information relevant to the design of the bridge must be considered during preparation of the T,S,&L and included in the plans when applicable.

- A. English - All plans must be developed in English units of measure.
- B. General Plan of Site Sheet
 - 1. Traffic Data (present & future ADTs, posted & design speeds, % commercial)
 - 2. Township, Section, and Range
 - 3. Design Loading
 - 4. Plan View of Project
 - a) Stations Shown (include P.O.B. & P.O.E.)
 - b) Utilities
 - c) Flow direction and name of water course (if applicable)
 - d) North Arrow
 - e) Layout of Bridge
 - 1) deck
 - 2) approach
 - 3) wingwalls
 - 4) guardrail
 - f) Survey and Construction Centerlines
 - g) Horizontal Alignment and/or Alignment Diagram
 - h) Outline of Existing Bridge
 - i) Topography
 - 5. Elevation View
 - a) Vertical Alignment
 - 1) All vertical curve data
 - a) Grade Left
 - b) Grade Right
 - c) Length
 - d) K value computed
 - 2) Existing and Proposed Alignments
 - 3) Existing Grades just outside the P.O.B. & P.O.E.
 - b) Span Lengths
 - c) Reference Point Stations and Elevations
 - d) Project Limits (include labels for P.O.B. and P.O.E.)

- e) Abutment/Pier Type
 - f) Bottom of Abutment, Pier Footing Elevations
 - g) Pile Information: Capacity and Type (if applicable)
 - h) Water Surface Information (survey elevation & date and 100 year elevation)
 - i) Rip Rap
 - j) Stations and Elevations
 - k) Proposed Low Beam Elevation
- 6. Benchmark Box
 - 7. Existing Structure Information
 - 8. Control Points or Horizontal Tie Points
 - 9. Construction Staging Details (if applicable)
- C. Preliminary Soils Data – If available at the TS&L stage. Soil borings are to be obtained as soon as possible after the T,S,&L review, and prior to submitting GI plans.
- D. Waterway data (for water crossings).
- 1. Hydraulic table - to be completed for stream and river crossings, as shown in the MDOT Bridge Design Manual (including the 50 year and 100 year flood data for the existing and proposed structure). The design must be compatible with the appropriate downstream stream section.
 - 2. Stream bank alignment is to be shown.
 - 3. Scour - Any evidence of scour on the existing structure and/or river banks should be noted.
 - 4. Recreational activities on the waterway, i.e. canoes, etc., must be considered in the design.
 - 5. Local authority for the watercourse and any local ordinances must be considered (County Drain Commission, etc.).
 - 6. Waterway data for structures crossing lake channels with negligible hydraulic flow should include:
 - a. Lake surface elevations, especially if varies at different times of the year.
 - b. Navigational opening under the bridge (width and height at a particular elevation).
 - c. Water surface elevation for a 100 year event.

E. General Plan of Structure Details

1. Typical Bridge Cross Section
 - a) Lane and Shoulder Widths shown: include centerline label
 - b) Shoulder to Fascia Distances dimensioned
 - c) Centerline to Fascia Distances dimensioned
 - d) Out to Out of Fascia dimensioned
 - e) Sidewalk dimensions (if applicable)
 - f) Deck Material and Thickness shown
 - g) Deck Cross Slope shown
 - h) Railing Type indicated
 - i) Number and Type of Beam shown
 - j) Earth Slopes shown (include existing and proposed)
 - k) Rip Rap shown
 - l) Pile Type and Capacity shown (include pile batter)
 - m) Limits of Backfill and Excavation shown
 - n) Cofferdams shown
2. Approach Typical
 - a) Lane and Shoulder widths
 - b) Guardrail Type
 - c) Road/Subbase Material

F. Participation limits.

The T,S,&L plans will either be found acceptable as is, acceptable subject to comments, or not acceptable, the latter requiring revisions to be made and the T,S,&L resubmitted.

Acceptance of the preliminary and final plans will be contingent upon consideration of the T,S,&L review comments, issuance of the MDEQ permit, review of the geotechnical information, and any other information which may become available after the T,S,&L submittal.

For Grade Inspection requirements see document titled “Items Required for Grade Inspection” on the MDOT’s Local Government Agencies website.